

AIR CONDITIONER SPLIT SYSTEMS





	 13.4 SEER2 AC COPELAND SCROLL™ COMPRESSOR REMOVABLE TOP GRILLE ASSEMBLY HIGH PRESSURE SWITCH HEAVY DUTY PSC MOTOR 1.5T - 5T SIZES
	1035887W WSA3BD4M1SN18K 1035888W WSA3BD4M1SN24K
	1035889W WSA3BD4MISN24K
μ	1035890W WSA3BD4M1SN36K
)	1035891W WSA3BD4M1SN42K
Department of the second s	1035892W WSA3BD4M1SN48K
	1035893W WSA3BD4M2SN60K

Model Numb	ber WSA3BD4M	1SN18K	1SN24K	1SN30K	1SN36K	1SN42K	1SN48K	2SN60K	
Volts-Cycles-Phase (1) 208/230-60-1									
	Delay Fuse Max.	(2)	20	25	30	30	40	50	60
Electrical Data	Min. Circuit Ampa	city	11.6	14.3	17.7	19.1	24.7	32.7	35.0
Dala	Comp. Locked Ro	tor Amp	47.5	62.9	72.5	87.4	110.0	105.3	139.9
	Fan Motor HP		1/20	1/20	1/10	1/8	1/4	1/4	1/4
Refrigerant s	suction line O.D.	0-24 ft.	5/8" (3)	3/4"	3/4"	3/4"	7/8"	7/8"	7/8"
	line is 3/8" O.D. for	25-39 ft.	5/8" (3)	3/4"	3/4"	3/4"	7/8"	7/8"	7/8"
entire length.	entire length. 40-75 ft.			3/4"	3/4"	7/8" (4)	7/8"	1-1/8" (5)	1=1/8" (5)
Approximate Weight (Ibs.) Ship			121	138	162	166	198	214	226
Sound Ratin	g dBA		73	73	78	79	79	79	79

MATCHES WITH...

C74B(A,H)MX



1.5T-5T SIZES

FACTORY-INSTALLED TXV
H = HORIZONTAL/MULTIPOISE
A = VERTICAL
CASED
1,5T-5T SIZES

B64BMMO Image: Piston-driven Multi-poised Multi-speed Durable, attractive cabinet 1.5t - 4t sizes

FSA3BD		CROLL™ COMPRESSOR IENDLY JACKET JRE SWITCH PSC MOTOR
	1035887F 1035888F 1035889F 1035890F 1035891F 1035892F 1035893F	FSA3BD4M1SN18K FSA3BD4M1SN24K FSA3BD4M1SN30K FSA3BD4M1SN36K FSA3BD4M1SN42K FSA3BD4M1SN48K FSA3BD4M1SN48K

Model Numbe	odel Number FSA3BD4M			1SN24K	1SN30K	1SN36K	1SN42K	1SN48K	2SN60K
	Volts-Cycles-Phas	se (1)				208/230-60-1			
	Delay Fuse Max.	(2)	20	25	30	30	40	50	60
Electrical Data	Min. Circuit Ampa	city	11.6	14.3	17.7	19.1	24.7	32.7	35.0
Data	Comp. Locked Ro	tor Amp	47.5	62.9	72.5	87.4	110.0	105.3	139.9
	Fan Motor HP		1/20	1/20	1/10	1/8	1/4	1/4	1/4
Refrigerant su	uction line O.D.	0-24 ft.	5/8" (3)	3/4"	3/4"	3/4"	7/8"	7/8"	7/8"
	ine is 3/8" O.D. for	25-39 ft.	5/8" (3)	3/4"	3/4"	3/4"	7/8"	7/8"	7/8"
entire length.		40-75 ft.	3/4"	3/4"	3/4"	7/8" (4)	7/8"	1-1/8" (5)	1-1/8" (5)
Approximate Weight (Ibs.) Ship		121	138	162	166	198	214	226	
Sound Rating	Sound Rating dBA		72	72	73	74	74	74	75

MATCHES WITH...



• 1.5T-5T SIZES



• 1.5T-5T SIZES

B64BMMO Filter of the second state of the sec

WSA3BE	 13.8 SEER2 AC COPELAND SCROLL™ COMPRESSOR REMOVABLE TOP GRILLE ASSEMBLY HIGH PRESSURE SWITCH HEAVY DUTY PSC MOTOR 1.5T - 5T SIZES
	1035862W WSA3BE4M1SN18K
	1035863W WSA3BE4M1SN24K 1035864W WSA3BE4M1SN30K
	1035865W WSA3BE4M1SN36K
H	1035866W WSA3BE4M1SN42K
	1035867W WSA3BE4M1SN48K
	1035868W WSA3BE4M2SN60K

Model Number WSA3BE			18K	24K	30K	36K	42K	48K	60K		
	Volts-Cycles-Phase ((1)	208/230-60-1								
Electrical Data	Delay Fuse Max. (2)		20	25	25	30	40	45	60		
	Min. Circuit Ampacity	12.1	15.4	16.9	18.6	23.5	26.2	36.2			
Common the Data	Fan Motor	HP	1/8	1/8	1/8	1/5	1/4	1/4	1/3		
Component Data	Compressor Data	LRA	42.6	61.0	65.0	87.4	110.2	110.0	171.0		
Refrigerant suction li	ne O.D.	0-24 ft.	3/4"	3/4"	3/4"	3/4"	7/8"	7/8"	7/8"		
NOTE: Liquid line is 3/8		25-39 ft.	3/4"	3/4"	3/4"	7/8" (3)	7/8"	7/8"	1-1/8" (4)		
length."		40-75 ft.	3/4"	3/4"	3/4"	7/8" (3)	7/8"	7/8"	1-1/8" (4)		
Approximate Shipping Weight (Ibs.)		187	192	197	225	273	264	268			
Sound Rating db			69	69	69	71	73	74	75		

MATCHES WITH



• 1.5T-5T SIZES



• 1.5T-5T SIZES



FSASBF	 2-STA ULTRA SWEPT SERVIO HIGH & SWITC 	TECH™ C I WING FA CER FRIEN & LOW PRI CHES RESSOR S	DLY JACKET	R
	103595 103595 103595 103595	56F 57F	FSA3BF4M FSA3BF4M FSA3BF4M FSA3BF4M	2SN36K 2SN48K
Model Number FSA3BF4M	2SN24K	2SN36K	2SN48K	2SN60K
Volts-Cycles-Phase (1)		208/2	30-60-1	

	Volts-Cycles-Pha	ase (1)		208/23	30-60-1	
Flootrical	Delay Fuse Max	. (2)	25	30	45	60
Electrical Data	Min. Circuit Amp	Min. Circuit Ampacity		19.1	28.0	34.6
Dala	Comp. Locked R	lotor Amp	62.9	84.2	122.1	158.0
	Fan Motor HP		1/8	1/4	1/3	1/3
Refrigerant suc	ction line O.D.	0-24 ft.	3/4"	3/4"	7/8"	7/8"
NOTE: Liquid lin	ie is 3/8" O.D. for	25-39 ft.	3/4"	3/4"	7/8"	7/8"
entire length.		40-75 ft.	3/4"	3/4"	7/8"	1-1/8" (3)
Approximate W	eight (Ibs.)	Ship	153	208	240	246
Sound Ratings	dBA		71	76	76	76

MATCHES WITH...





B64VMMX



C74B(A,H)MO	 ORIFICE R410A CASED OR UNCASED 1.5T-5T SIZES A = "A" VERTICAL H = HORIZONTAL/MULTIPOISED 				
	CABINET SIZES A - 14.25 IN B - 17.50 IN C - 21 IN D - 24.50 IN	ACCESSORIES • TXV KITS • LIQUID LINE TUBE KITS • HORIZONTAL DRAIN PAN KITS			

"A" COIL SPECIFICATIONS

C74BAM	018C-A	02430C-A	018C-B	02430С-В	03642С-В	02430C-C	03642C-C	048C-C	042C-D	048C-D
NOMINAL CAPACITY, MIN BTUH	10.000	24,000	10.000	24,000	36,000	24,000	36,000	40.000	40.000	40.000
NOMINAL CAPACITY, MAX BTUH	18,000	30,000	18,000	30,000	42,000	30,000	42,000	48,000	42,000	48,000
INSTALLED ORIFICE SIZE (IN.)	0.046	0.053	0.046	0.053	0.068	0.053	0.068	0.077	0.068	0.077
W - WIDTH (IN.)	14.25	14.25	17.5	17.5	17.5	21	21	21	24.5	24.5
H - HEIGHT (IN.)	20.75	20.75	20.75	20.75	26.75	26.75	26.75	30.25	30.25	30.25
HL - HEIGHT OF LIQUID LINE (IN.)	17.5	17.5	17.5	17.5	23.5	23.5	23.5	27	27	27
HS - HEIGHT OF SUCTION LINE (IN.)	15.5	15.5	15.5	15.5	21.5	21.5	21.5	25	25	25
CONNECTION - LIQUID LINE	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8
CONNECTION - SUCTION LINE	3/4	3/4	3/4	3/4	7/8	7/8	7/8	7/8	7/8	7/8
HORIZONTAL DRAIN PAN KIT (4)	920265	920265	920265	920265	920266	920266	920266	920267	920267	920267

"H" COIL SPECIFICATIONS

C74BHM	018C-A	02430C-A	018C-B	02430C-B	03642С-В	02430C-C	03642C-C	048C-C	042C-D	048C-D
NOMINAL CAPACITY, MIN BTUH	18,000	24,000	18,000	24,000	36,000	24,000	36,000	48.000	40.000	48.000
NOMINAL CAPACITY, MAX BTUH	18,000	30,000	18,000	30,000	42,000	30,000	42,000	48,000	42,000	48,000
INSTALLED ORIFICE SIZE (IN.)	0.046	0.053	0.046	0.053	0.068	0.053	0.068	0.077	0.068	0.077
W - WIDTH (IN.)	14.25	14.25	17.5	17.5	17.5	21	21	21	24.5	24.5
H - HEIGHT (IN.)	26.75	26.75	26.75	26.75	26.75	26.75	26.75	30.25	30.25	30.25
HL - HEIGHT OF LIQUID LINE (IN.)	23.5	23.5	23.5	23.5	23.5	23.5	23.5	27	27	27
HS - HEIGHT OF SUCTION LINE (IN.)	21.5	21.5	21.5	21.5	21.5	21.5	21.5	25	25	25
CONNECTION - LIQUID LINE	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8
CONNECTION - SUCTION LINE	3/4	3/4	3/4	3/4	7/8	7/8	7/8	7/8	7/8	7/8

C74B(A,H)MX	 FACTORY-INSTA R410A H = HORIZONTAL/ A = VERTICAL CASED ONLY 1.5T-5T SIZES 	
	CABINET SIZES A - 14.25 IN B - 17.50 IN C - 21 IN D - 24.50 IN	ACCESSORIES • LIQUID LINE TUBE KITS • HORIZONTAL DRAIN PAN KITS

"A" COIL SPECIFICATIONS													
C74BAM	X24C-A	X30C-A	Х24С-В	Х30С-В	Х36С-В	X30C-C	X36C-C	X42C-C	X48C-C	X60C-C	X42C-D	X48C-D	X60C-D
NOMINAL CAPACITY, BTUH	24,000	30,000	24,000	30,000	36,000	30,000	36,000	42,000	48,000	60,000	42,000	48,000	60,000
METERING DEVICE	TXV												
W - WIDTH (IN.)	14.25	14.25	17.5	17.5	17.5	21	21	21	21	21	24.5	24.5	24.5
H - HEIGHT (IN.)	20.75	20.75	20.75	20.75	26.75	26.75	26.75	26.75	30.25	30.25	30.25	30.25	30.25
HL - HEIGHT OF LIQUID LINE (IN.)	17.5	17.5	17.5	17.5	23.5	23.5	23.5	23.5	27	27	27	27	27
HS - HEIGHT OF SUCTION LINE (IN.)	15.5	15.5	15.5	15.5	21.5	21.5	21.5	21.5	25	25	25	25	25
CONNECTION - LIQUID LINE	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8
CONNECTION - SUCTION LINE	3/4	3/4	3/4	3/4	7/8	3/4	7/8	7/8	7/8	7/8	7/8	7/8	7/8
HORIZONTAL DRAIN PAN KIT	920265	920265	920265	920265	920266	920265	920266	920266	920267	920267	920266	920267	920267

"H" COIL SPECIFICATIONS

C74BHM	X24C-A	X30C-A	X24C-B	Х30С-В	Х36С-В	X30C-C	X36C-C	X42C-C	X48C-C	X60C-C	X42C-D	X48C-D	X60C-D
NOMINAL CAPACITY, BTUH	24,000	30,000	24,000	30,000	36,000	30,000	36,000	42,000	48,000	60,000	42,000	48,000	60,000
METERING DEVICE	TXV	ТХУ	TXV	TXV	TXV	TXV	TXV						
W - WIDTH (IN.)	14.25	14.25	17.5	17.5	17.5	21	21	21	21	21	24.5	24.5	24.5
H - HEIGHT (IN.)	26.75	26.75	26.75	26.75	26.75	26.75	26.75	26.75	30.25	30.25	30.25	30.25	30.25
HL - HEIGHT OF LIQUID LINE (IN.)	23.5	23.5	23.5	23.5	23.5	23.5	23.5	23.5	27	27	27	27	27
HS - HEIGHT OF SUCTION LINE (IN.)	21.5	21.5	21.5	21.5	21.5	21.5	21.5	21.5	25	25	25	25	25
CONNECTION - LIQUID LINE	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8
CONNECTION - SUCTION LINE	3/4	3/4	3/4	3/4	7/8	3/4	7/8	7/8	7/8	7/8	7/8	7/8	7/8

WHY CHOOSE US?



90 DAY

PRODUCT

ASSURANCE COMMITMENT

AireForce

LIFETIME

WARRANTY

AireForce

STANDING BEHIND YOUR INVESTMENT

AIREFORCE SPLIT SYSTEM AIR CONDITIONERS, HEAT PUMPS, AND GAS FURNACES OFFER A 10-YEAR PARTS AND COMPRESSOR WARRANTY WHEN REGISTERED AS PART OF A COMPLETE AIREFORCE SYSTEM.

CONFIDENCE IN OUR PRODUCTS

TO PROVE OUR CONFIDENCE IN OUR PRODUCTS, WE PROVIDE A 90-DAY PROTECTION PLAN TO HELP ASSIST WITH THE COST OF ANY PRODUCT FAILURES ON ALL AIREFORCE EQUIPMENT.

PRODUCTS YOU CAN COUNT ON

HEAT EXCHANGER WHEN YOU REGISTER YOUR NEW AIREFORCE FURNACE OR GAS/ELECTRIC PACKAGED SYSTEM, WE EXTEND THE HEAT EXCHANGER WARRANTY FROM 20 YEARS TO OUR LIFETIME HEAT EXCHANGER WARRANTY.



AireForce

A COMMITMENT TO QUALITY

IF THE HEAT EXCHANGER IN YOUR GAS FURNACE FAILS WITHIN THE FIRST YEAR, WE'LL REPLACE THE PRODUCT WITH LIKE PRODUCT UNDER THE AIREFORCE QUALITY PLEDGE.



AIREFORCE.COM

© ALL RIGHTS RESERVED 2023 - AIREFORCE: YOUR TRUSTED HVAC SOURCE