

RIBME2401B

LED ON = RELAY ACTIVATED

Bulletin B534 • 393019B

CONTROL
INPUT



COIL

Common



5-25 Vac/dc



Common



24 Vac/dc

POWER
INPUT



120 Vac

**Functional
Devices, Inc.**



Functional Devices, Inc.
310 South Union Street
Russiaville, IN 46979
Phone: (765)883-5538 Fax: (765)883-7505

CONTACT RATINGS

20A Res. @ 277 Vac

1 HP @ 120 Vac

2 HP @ 277 Vac

20A Ball. @ 120/277 Vac (N/O)

10A Ball. @ 120/277 Vac (N/C)

16A Elect. Ball. @ 277 Vac (N/O)

10A Tung. @ 120 Vac (N/O)

770 VA Pilot @ 120 Vac

1110 VA Pilot @ 277 Vac

CONTROL INPUT

.4mA @ 5Vdc

.9mA @ 10Vdc

1mA @ 12Vdc

2mA @ 24Vdc

3mA @ 24Vac

POWER INPUT

47mA @ 30Vdc

83mA @ 24Vac

47mA @ 120Vac

SIGNALING
 US
LISTED
13CY
15M6

TYPE F, G, EM

For use with
Smoke Control System
General Signaling
Equip. NM

CONTACTS

Common

N/O

N/C

FOR SUPPLY CONNECTIONS USE # 12 AWG OR
LARGER WIRES RATED AT LEAST 75°C (167°F).

www.functionaldevices.com