



Safety & Specialty Products

# Carbon Monoxide Monitor Snifit®+



Actual size

## Features & Benefits:

- Rugged, reliable long-running performance provides instant carbon monoxide monitoring with a range of 0 - 2,000 ppm
- User-adjustable alarms provide visual (flashing LEDs), audible, and vibrating alerts for low/high, STEL and TWA conditions
- Graphic display shows CO concentrations in PPMs (0 - 999 ppm) and as % Vol. (from 1,000 - 2,000 ppm)
- Compact, lightweight size - only 3.6 oz. (105 g) including battery
- Display notification shows low battery, sensor life, and calibration status
- Metal lanyard loop and durable suspender clasp for easy attachment to clothing

## Continuous Carbon Monoxide Monitoring in a Compact Size

Snifit®+ is a compact personal safety monitor ideal for alerting users when potentially dangerous carbon monoxide conditions are detected. A rugged, impact-resistant housing helps to protect the unit against the rigors of daily field use and is sealed for an IP65 environmental resistance rating. It is also designed to meet UL 913 specifications and to provide at least 2 years of continuous maintenance-free operation under normal operating conditions.

The Snifit®+ features high and low alarms with distinctive alert intervals to notify the user of unsafe conditions via audible (90dB), visual (bright flashing LEDs) and vibrating indicators. Built-in short-term exposure limit (STEL) and time-weighted average (TWA) alarms provide additional margins of user safety. Preset low/high alarms can be adjusted by the user or left at the factory set defaults of 35 ppm and 200 ppm.

Ideal for HVAC service technicians and utility personnel, Snifit®+ is the affordable tool for detecting and measuring ambient air CO levels in rooms or garages or around combustion appliances like furnaces, stoves and water heaters.

## Specifications

### Snifit® + Personal Carbon Monoxide Monitor

<b>Measurement Range:</b> <b>Carbon Monoxide</b>	0 - 2,000 ppm; Displayed as <b>ppm</b> from 0-999 ppm; <b>% vol</b> from 1,000-2,000 ppm
<b>Sensor Type:</b>	Electrochemical
<b>Operating Temperature:</b>	-4° F to 122° F (-20° C to 50° C)
<b>Humidity:</b>	15 to 90% RH (non-condensing)
<b>Duty Cycle:</b>	Continuous running
<b>Response:</b>	T90 <30 seconds
<b>Alarm: Visual</b>	Flashing; Red LED alerts; 270° viewable
<b>Alarm: Audible</b>	Beeping; 90 dB @ 12"
<b>Alarm: Vibrating</b>	Repeating
<b>Alarms: Low / High</b>	Factory-set defaults 35 ppm / 200 ppm; user-adjustable
<b>Dimensions:</b>	3.81"h x 2.31"w x 0.80"d (9.67 cm x 5.87 cm x 2.0 cm)
<b>Weight:</b>	3.6 oz. including battery (105 kg)
<b>Power:</b>	Lithium battery (included)
<b>Run Time:</b>	2+ years, continuous; standard operation
<b>Housing:</b>	IP65 environmental resistance; dirt and moisture protection Rubberized, impact-resistant enclosure
<b>Approvals:</b>	CE mark, Designed to meet UL 913 specifications
<b>Warranty:</b>	Instrument, CO Sensor - 2 Years

## Snifit® + Ordering Information

<b>0019-7600</b>	Snifit®+ Carbon Monoxide Monitor Kit (includes battery)
<b>0019-6106</b>	Snifit®+ Calibration Adapter
<b>0051-2978</b>	CO Calibration Kit (regulator and tubing)
<b>0051-1994</b>	Calibration Gas: 100 ppm CO

Made in USA



Distributed By:



 BACHARACH IS A U.S. BASED MANUFACTURER

©2013, Bacharach, Inc., all rights reserved. All information is subject to verification.  
November 2013 - REV. 1 Printed in U.S.A.

