



## 24-300: BRONZE LIQUID LEVEL GAUGES

### OVERVIEW

Automatic and non-automatic direct reading gauges in shank pipe sizes 1/2" and 3/4".



### FEATURES

- Heavy pattern bronze valve body
- Guard rod bracket to accommodate four guard rods
- PTFE reinforced gauge glass gasket and stem packing are standard
- Rated 250 psig @ 400°F, 500 psig @ 100°F (See note!)
- Automatic - conforms to ASME power boiler code requirements for automatic water gauges; ball checks in upper and lower arms
- High pressure gauge glass and gaskets are standard
- CRN Registered
- Bronze ball valve drains are standard

	Part Number	Pipe Size (in.)	Glass O.D. & Length	Wt./100 (lbs.)	Wheel Type
Non-Automatic	24-301-00	1/2	5/8 x 12	425	ALUMINUM
	24-302-00	1/2	5/8 x 12	425	COMPOSITION
	24-304-00	3/4	3/4 x 16	490	ALUMINUM
	24-305-00	3/4	3/4 x 16	490	COMPOSITION
ASME Automatic	24-350-00**	1/2	5/8 x 12	425	ALUMINUM
	24-351-00**	1/2	5/8 x 12	425	COMPOSITION
	24-353-00**	3/4	3/4 x 16	490	ALUMINUM
	24-354-00**	3/4	3/4 x 16	490	COMPOSITION

Note: Service ratings are subject to pressure/temperature ratings of gauge glass and glass gaskets.  
 \*\* Conforms to ASME Check Requirements

### OPTIONS

Suffix Number	Specification
-00	Standard gauge w/ standard glass & rod
-01	Top only
-02	Bottom only
-03	Standard gauge less glass & rod
-10	For special gauges w/ non-standard glass and rod lengths