

DPE SERIES DRIP PAN ELBOW

Job Name:	Contractor:
Job Location:	P.O. Number:
Engineer:	Representative:
Tag:	Wholesale Distributor:

DESCRIPTION

Drip Pan Elbows connect to the safety valve outlet and direct steam discharge into the discharge piping, allowing condensate to drain away. Isolates the valve from piping stresses. Highly recommended in steam service.

FEATURES

- □ Black corrosion resistant finish
- □ 3/4" thru 8" Inlet connections

MATERIALS

Cast Iron, ASTM A126-B


ORDER NUMBER

DPE- Suffix

Suffix Options

- ☐ 07 = 3/4" NPT Inlet
- ☐ 10 = 1" NPT Inlet
- ☐ 12 = 1-1/4" NPT Inlet
- ☐ 15 = 1-1/2" NPT Inlet
- ☐ 20 = 2" NPT Inlet
- ☐ 25 = 2-1/2" NPT Inlet
- ☐ 30 = 3" NPT Inlet
- ☐ 40 = 4" NPT Inlet
- ☐ 60 = 6" ANSI Class 125 Flange
- ☐ 80 = 8" ANSI Class 125 Flange





APOLLO	INLET	А	В	С	D	E	F	G	WEIGHT
PART#	in (mm)	in (mm)	in (mm)	in (mm)	in (m m)	in (mm)	in (mm)	NPT	LB (kg)
DPE07	3/4 (20)	2.00 (51)	3.75 (95)	1.88 (48)	2.00 (51)	1.00 (25)	1.50 (38)	1/4	2 (1)
DPE10	1 (25)	2.00 (51)	3.75 (95)	1.88 (48)	2.00 (51)	1.00 (25)	1.50 (38)	1/4	2 (1)
DPE12	1-1/4 (32)	2.00 (51)	5.50 (140)	2.47 (63)	4.13 (105)	1.44 (37)	2.13 (54)	3/8	7.5 (3)
DPE15	1-1/2 (40)	2.00 (51)	5.50 (140)	2.47 (63)	4.13 (105)	1.44 (37)	2.13 (54)	3/8	7.5 (3)
DPE20	2 (50)	3.00 (76)	6.25 (159)	2.31 (59)	3.63 (92)	1.63 (41)	2.25 (57)	1/2	8.5 (4)
DPE25	2-1/2 (65)	4.00 (102)	7.38 (187)	3.00 (76)	4.31 (109)	1.94 (49)	2.69 (68)	3/4	12 (5)
DPE30	3 (80)	4.00 (102)	8.00 (203)	3.50 (89)	4.88 (124)	2.31 (59)	3.13 (80)	3/4	19 (9)
DPE40	4 (100)	6.00 (152)	9.63 (245)	4.50 (114)	5.75 (146)	2.88 (73)	3.75 (95)	3/4	25 (11)
DPE60	6 (150)	8.00 (203)	12.75 (324)	6.63 (168)	7.44 (189)	4.19 (106)	8.00 (203)	3/4	105 (48)
DPE80	8 (200)	10.00 (254)	16.50 (419)	7.50 (191)	9.44 (240)	5.38 (137)	10.75 (273)	1	202 (92)

Conbraco Industries, Inc. 701 Matthews Mint Hill Rd. Matthews NC 28105 USA; www.apollovalves.com; 704-841-6000