## PRO PRO1 SUBMITTAL SHEET

Job Name:	Location:	Date:
Purchaser:		_ Installer:
Submitted to:		_ For: RNC R&R Commercial

## **MODEL T805**

Single Stage 1 Heat, 1 Cool Battery or Hardwire 7 Day, 5/1/1 or Non-Programmable

## This model features:

- 8 sq. inch display
- Blue backlight
- Glow in the dark light button
- Easy access battery compartment
- Keypad lockout
- Adjustable setpoint limits
- Simple private label badge system
- Easy access battery compartment

## Specifications:

Application Programmability Changeover Display Range Control Range Display Accuracy Heat Swing Cool Swing Terminals Load Rating Power Source

Operating Ambient Operating Humidity Mounting Dimensions Warranty • 5 Year Warranty

- Seperate heating and cooling swing (cycle rate) adjustments
- 5 minute compressor delay protection (selectable on or off)
- Universal subbase
- Battery or 24v power
- Programmable Fan

1 heat, 1 cool 7 Day, 5/1/1 or Non-Programmable System Switch 41°F to 95°F (5°C to 35°C) 44°F to 90°F (7°C to 32°C) +/-1°F Adjustable from 0.2°F to 2.0°F Adjustable from 0.2°F to 2.0°F Rc, Rh, G, Y, C, O, B, W 1 amp per terminal, 1.5 amp maximum all terminals combined 18 to 30 VAC, NEC Class II, 50/60 Hz for hardwire (common wire) Battery power from 2 AA Alkaline batteries 32°F to +105°F (0°C to +41°C) 90% non-condensing maximum Wall or Junction Box 4.7"W x 4.4"H x 1.1"D (119mm W x 112mm H x 28mm D) 5 year warranty

