


AC POWER SUPPLY

PSC40AB10

Enclosed Single 40 VA Power Supply, 120 to 24 Vac

PSC100AB10

Enclosed Single 100 VA Power Supply, 120 to 24 Vac



* Move internal jumper to "HOT" position if you wish outlets to always be hot otherwise outlets will be switched by main breaker.



Shown Without Cover

Shown With Cover



LISTED Class 2



Made in USA Meets "Buy American" of ARRA 2009

POWER SUPPLIES

SPECIFICATIONS

Transformer: One 40 VA Split-Bobbin, Inherently Limited (PSC40AB10)
One 100 VA Split-Bobbin, Circuit Breaker (PSC100AB10)
Primary: 120 Vac
Secondary: 24 Vac, w/ LED Indicator
Frequency: 50/60 Hz
24 Vac ON/OFF: On / Off Switch & Breaker

Main Breaker ON/OFF: Switch / Breaker (10 Amp) (Kills power to entire unit: Outlets, Aux. Output, & Transformer)*
Total Combined Output 9A
Mounting: Mounting plate included (as shown)
Approvals: Class 2 (UL Approved UL5085-3), UL916, UL508, C-UL, CE, RoHS
Dimensions: 6.250" x 5.620" x 4.250"
Weight: 4.40 lbs. (PSC40AB10)
5.80 lbs. (PSC100AB10)

Notes:
• To order without enclosure, see PSB40AB10 & PSB100AB10.
• To order UL508, add "-IC" to end of model number.