




AC CURRENT SWITCHES

RIBMXRF

4.00" Track Mount Solid Ring Remote **Fixed**
3-150 Amp AC Sensor, Self-Powered

RIBMXRA

4.00" Track Mount Solid Ring Remote **Adjustable**
3-150 Amp AC Sensor, Self-Powered



SPECIFICATIONS

Operating Temperature: -30 to 140° F
Humidity Range: 5 to 95% (noncondensing)
Dimensions: 1.700" x 4.000" x 1.250"
Track Mount: 4.000", See MT4 Series on page 152
MT4 Mounting Track Sold Separately
Wire Length: 16", 600V Rated
Approvals: UL Listed, UL916, UL864, C-UL
 California State Fire Marshal, CE, RoHS

Sensor Type: External, with contact status
Inside Diameter: .75"
Outside Diameter: 2.28"
Sensor Threshold: Fixed, 3 Amps (RIBMXRF)
 Adjustable, 3-150 Amps (RIBMXRA)
Sensor Range: 3-150 Amps
Max Sense Voltage: 600 Vac
Sensor Contact Status: Current below threshold: Open / LED OFF
 Current above threshold: Closed / LED ON

Sensor Contact:

- Solid State Contact
- 30 Vac/dc, .4 Amp Max.
- When sensor contact is off (open), leakage <30 uA @ 30Vac/dc
- When sensor contact is on (closed), voltage drop < .3 Vac/dc @ .1 Amp
< 1.6 Vac/dc @ .4 Amp

CURRENT SENSORS