



# Full Circle<sup>®</sup> Repair Clamp

## All Stainless Steel, Fabricated Lugs, Single Band

# 261



**Description:** A single-band clamp designed to provide 360° pressure and complete leak repair

**Application:** Works on Cast Iron, Ductile Iron, Steel, Asbestos Cement, Copper, Aluminum, PVC, HDPE, Fiberglass and other pipe types.

### Key Features:

- Designed with "hot" soils in mind
- Standard widths 7.5" through 30"
- Can be used to repair pipe or join pipe ends
- Can be manufactured to odd size pipe O.D.'s
- All 304 Stainless Steel construction for corrosion resistance
- A 360° Gasket seal provides maximum support and reinforcement
- Keeper bar helps pull clamp around the pipe and closes the clamp during installation
- Range up to .40"
- Larger clamps have a greater range to help reduce inventory

### Materials Specifications (subject to change):

BAND: Stainless Steel (Type 304)

LUGS: Stainless Steel (Type 304)

KEEPER BARS: Stainless Steel (Type 304)

GASKET: Nitrile (Buna N) to produce superior storage and performance characteristics while resisting water, acids, alkalies, most aliphatic hydrocarbon and other chemicals.

Temperature Range: -20°F to +180°F

BRIDGE PLATE: 304 Stainless Steel recessed flush and bonded to gasket

STUD BOLTS: Type 304 Stainless Steel Epoxy coated

NUTS: fluoropolymer coated to prevent galling

*Also in metric sizes. HDPE applications require clamps with spring washers*

**Working Pressure:** Up to 150 PSI

### Pipe Applications:

Cast Iron, Ductile Iron, Asbestos Cement, PVC, HDPE, Steel, Copper, Fiberglass and other types of pipes

**Sizes (in inches):** 2, 2¼-2½, 3, 4, 4-5, 6, 8, 10, 12



**THIS PRODUCT DOES NOT RESTRAIN PIPE MOVEMENT.** Proper anchoring is required to prevent pipe pullout. Failure to anchor or improper anchoring can result in dangerous pipe content escape, property damage, serious injury, or death. Read the product installation instructions prior to installing this product.



# Full Circle<sup>®</sup> Repair Clamp

## All Stainless Steel, Fabricated Lugs, Single Band

261

STANDARD				CATALOG NUMBER	METRIC			
NOM. SIZE INCHES	O.D. RANGE INCHES	WIDTH INCHES	WT. EACH LBS.		NOM. SIZE MM	O.D. RANGE MM	WIDTH MM	WT. EACH KG.
2	2.35-2.63	7.5	5	261-00023807-000	50	60-67	190	2.1
	2.35-2.63 2.35-2.63	10 12.5	6 8	261-00023810-000 261-00023812-000		60-67 60-67	254 317	2.9 3.5
	2.35-2.63	15	9	261-00023815-000		60-67	381	4.3
2 1/4-2 1/2	2.70-3.00	7.5	5	261-00027507-000	65	70-77	190	2.1
	2.70-3.00 2.70-3.00	10 12.5	6 8	261-00027510-000 261-00027512-000		70-77 70-77	254 317	2.9 3.5
	2.70-3.00	15	9	261-00027515-000		70-77	381	4.3
3	2.97-3.25	7.5	5	261-00030007-000	65	76-83	190	2.2
	2.97-3.25 2.97-3.25	10 12.5	6 8	261-00030010-000 261-00030012-000		76-83 76-83	254 317	2.9 3.6
	2.97-3.25	15	10	261-00030015-000		76-83	381	4.4
3	3.46-3.70	7.5	5	261-00035007-000	80	88-93	190	2.2
	3.46-3.70 3.46-3.70	10 12.5	7 8	261-00035010-000 261-00035012-000		88-93 88-93	254 317	3.0 3.7
	3.46-3.70	15	10	261-00035015-000		88-93	381	4.5
3-4	3.73-4.00	7.5	4	261-00037507-000	80-100	95-101	190	2.3
	3.73-4.00 3.73-4.00	10 12.5	7 9	261-00037510-000 261-00037512-000		95-101 95-101	254 317	3.1 3.9
	3.73-4.00	15	10	261-00037515-000		95-101	381	4.6
3-4	3.96-4.25	7.5	4	261-00040007-000	80-100	101-107	190	2.4
	3.96-4.25 3.96-4.25	10 12.5	7 9	261-00040010-000 261-00040012-000		101-107 101-107	254 317	3.1 4.0
	3.96-4.25	15	10	261-00040015-000		101-107	381	4.7
4	4.45-4.73	7.5	6	261-00045007-000	100	114-124	190	2.5
	4.45-4.73 4.45-4.73	10 12.5	7 9	261-00045010-000 261-00045012-000		114-124 114-124	254 317	3.3 4.2
	4.45-4.73	15	11	261-00045015-000		114-124	381	5.0
4	4.74-5.14	7.5	6	261-00048007-000	100	120-131	190	2.9
	4.74-5.14	10	8	261-00048010-000		120-131	254	3.8
	4.74-5.14	12.5	11	261-00048012-000		120-131	317	4.8
	4.74-5.14	15	13	261-00048015-000		120-131	381	5.7
	4.74-5.14	20	17	261-00048020-000		120-131	508	7.6
4-5	4.95-5.35	7.5	6	261-00050007-000	125	126-135	190	2.9
	4.95-5.35	10	8	261-00050010-000		126-135	254	3.8
	4.95-5.35	12.5	11	261-00050012-000		126-135	317	4.8
	4.95-5.35	15	13	261-00050015-000		126-135	381	5.7
	4.95-5.35	20	17	261-00050020-000		126-135	508	7.6

STANDARD				CATALOG NUMBER	METRIC			
NOM. SIZE INCHES	O.D. RANGE INCHES	WIDTH INCHES	WT. EACH LBS.		NOM. SIZE MM	O.D. RANGE MM	WIDTH MM	WT. EACH KG.
4-5	5.22-5.62	7.5	7	261-00052507-000	125	132-143	190	3.0
	5.22-5.62	10	9	261-00052510-000		132-143	254	4.0
	5.22-5.62	12.5	11	261-00052512-000		132-143	317	5.0
	5.22-5.62	15	14	261-00052515-000		132-143	381	6.0
	5.22-5.62	20	18	261-00052520-000		132-143	508	8.0
6	5.95-6.35	7.5	6	261-00060007-000	125	151-161	190	3.1
	5.95-6.35	10	9	261-00060010-000		151-161	254	4.2
	5.95-6.35	12.5	12	261-00060012-000		151-161	317	5.2
	5.95-6.35	15	13	261-00060015-000		151-161	381	6.3
	5.95-6.35	20	18	261-00060020-000		151-161	508	8.4
6	6.56-6.96	7.5	6	261-00066307-000	150	167-177	190	3.3
	6.56-6.96	10	10	261-00066310-000		167-177	254	4.4
	6.56-6.96	12.5	12	261-00066312-000		167-177	317	5.5
	6.56-6.96	15	15	261-00066315-000		167-177	381	6.6
	6.56-6.96	20	20	261-00066320-000		167-177	508	8.9
	6.56-6.96	25	24	261-00066325-000		167-177	635	11.1
	6.56-6.96	30	29	261-00066330-000		167-177	762	13.3
6	6.84-7.24	7.5	7	261-00069007-000	150	174-184	190	3.3
	6.84-7.24	10	10	261-00069010-000		174-184	254	4.4
	6.84-7.24	12.5	12	261-00069012-000		174-184	317	5.5
	6.84-7.24	15	15	261-00069015-000		174-184	381	6.6
	6.84-7.24	20	20	261-00069020-000		174-184	508	8.9
	6.84-7.24	25	24	261-00069025-000		174-184	635	11.1
	6.84-7.24	30	29	261-00069030-000		174-184	762	13.3
6	7.05-7.45	7.5	7	261-00071007-000	150	180-189	190	3.4
	7.05-7.45	10	10	261-00071010-000		180-189	254	4.5
	7.05-7.45	12.5	12	261-00071012-000		180-189	317	5.6
	7.05-7.45	15	15	261-00071015-000		180-189	381	6.7
	7.05-7.45	20	20	261-00071020-000		180-189	508	8.9
	7.05-7.45	25	25	261-00071025-000		180-189	635	11.2
	7.05-7.45	30	30	261-00071030-000		180-189	762	13.4
6	7.45-7.85	7.5	7	261-00074507-000	150	190-199	190	3.5
	7.45-7.85	10	10	261-00074510-000		190-199	254	4.7
	7.45-7.85	12.5	13	261-00074512-000		190-199	317	5.9
	7.45-7.85	15	16	261-00074515-000		190-199	381	7.1
	7.45-7.85	20	21	261-00074520-000		190-199	508	9.4
	7.45-7.85	25	25	261-00074525-000		190-199	635	11.8
	7.45-7.85	30	31	261-00074530-000		190-199	762	14.2

STANDARD				CATALOG NUMBER	METRIC			
NOM. SIZE INCHES	O.D. RANGE INCHES	WIDTH INCHES	WT. EACH LBS.		NOM. SIZE MM	O.D. RANGE MM	WIDTH MM	WT. EACH KG.
8	7.95-8.35	7.5	8	261-00080007-000	200	202-212	190	3.7
	7.95-8.35	10	11	261-00080010-000		202-212	254	5.0
	7.95-8.35	12.5	13	261-00080012-000		202-212	317	6.2
	7.95-8.35	15	16	261-00080015-000		202-212	381	7.5
	7.95-8.35	20	22	261-00080020-000		202-212	508	9.9
	7.95-8.35	25	27	261-00080025-000		202-212	635	12.4
	7.95-8.35	30	33	261-00080030-000		202-212	762	14.9
8	8.54-8.94	7.5	9	261-00086307-000	200	217-227	190	3.9
	8.54-8.94	10	11	261-00086310-000		217-227	254	5.1
	8.54-8.94	12.5	14	261-00086312-000		217-227	317	6.5
	8.54-8.94	15	17	261-00086315-000		217-227	381	7.7
	8.54-8.94	20	23	261-00086320-000		217-227	508	10.3
	8.54-8.94	25	28	261-00086325-000		217-227	635	12.9
	8.54-8.94	30	34	261-00086330-000		217-227	762	15.4
8	8.99-9.39	7.5	9	261-00090507-000	200	228-239	190	4.0
	8.99-9.39	10	12	261-00090510-000		228-239	254	5.3
	8.99-9.39	12.5	15	261-00090512-000		228-239	317	6.6
	8.99-9.39	15	17	261-00090515-000		228-239	381	7.9
	8.99-9.39	20	23	261-00090520-000		228-239	508	10.5
	8.99-9.39	25	29	261-00090525-000		228-239	635	13.2
	8.99-9.39	30	35	261-00090530-000		228-239	762	15.8
8	9.27-9.67	7.5	9	261-00094007-000	200	236-245	190	4.0
	9.27-9.67	10	12	261-00094010-000		236-245	254	5.3
	9.27-9.67	12.5	16	261-00094012-000		236-245	317	6.7
	9.27-9.67	15	18	261-00094015-000		236-245	381	8.0
	9.27-9.67	20	24	261-00094020-000		236-245	508	10.7
	9.27-9.67	25	29	261-00094025-000		236-245	635	13.2
	9.27-9.67	30	35	261-00094030-000		236-245	762	16.0
8-10	9.70-10.10	7.5	9	261-00100007-000	225	247-256	190	4.2
	9.70-10.10	10	12	261-00100010-000		247-256	254	5.6
	9.70-10.10	12.5	16	261-00100012-000		247-256	317	7.0
	9.70-10.10	15	19	261-00100015-000		247-256	381	8.4
	9.70-10.10	20	25	261-00100020-000		247-256	508	11.3
	9.70-10.10	25	31	261-00100025-000		247-256	635	14.1
	9.70-10.10	30	37	261-00100030-000		247-256	762	16.9
10	10.64-11.04	7.5	10	261-00107507-000	250	270-280	190	4.5
	10.64-11.04	10	13	261-00107510-000		270-280	254	6.0
	10.64-11.04	12.5	16	261-00107512-000		270-280	317	7.4
	10.64-11.04	15	19	261-00107515-000		270-280	381	8.9
	10.64-11.04	20	24	261-00107520-000		270-280	508	11.9
	10.64-11.04	25	33	261-00107525-000		270-280	635	14.8
	10.64-11.04	30	39	261-00107530-000		270-280	762	17.8

STANDARD				CATALOG NUMBER	METRIC			
NOM. SIZE INCHES	O.D. RANGE INCHES	WIDTH INCHES	WT. EACH LBS.		NOM. SIZE MM	O.D. RANGE MM	WIDTH MM	WT. EACH KG.
10	11.04-11.44	7.5	10	261-00111007-000	250	280-291	190	4.5
	11.04-11.44	10	13	261-00111010-000		280-291	254	6.0
	11.04-11.44	12.5	17	261-00111012-000		280-291	317	7.5
	11.04-11.44	15	20	261-00111015-000		280-291	381	9.0
	11.04-11.44	20	26	261-00111020-000		280-291	508	12.0
	11.04-11.44	25	33	261-00111025-000		280-291	635	15.0
	11.04-11.44	30	40	261-00111030-000		280-291	762	18.0
10	11.34-11.74	7.5	10	261-00114007-000	250	288-299	190	4.6
	11.34-11.74	10	14	261-00114010-000		288-299	254	6.2
	11.34-11.74	12.5	17	261-00114012-000		288-299	317	7.7
	11.34-11.74	15	20	261-00114015-000		288-299	381	9.3
	11.34-11.74	20	27	261-00114020-000		288-299	508	12.4
	11.34-11.74	25	35	261-00114025-000		288-299	635	15.7
	11.34-11.74	30	42	261-00114030-000		288-299	762	18.5
10	11.75-12.15	7.5	10	261-00117507-000	250	298-309	190	4.7
	11.75-12.15	10	14	261-00117510-000		298-309	254	6.3
	11.75-12.15	12.5	17	261-00117512-000		298-309	317	7.9
	11.75-12.15	15	21	261-00117515-000		298-309	381	9.4
	11.75-12.15	20	28	261-00117520-000		298-309	508	12.6
	11.75-12.15	25	35	261-00117525-000		298-309	635	15.7
	11.75-12.15	30	42	261-00117530-000		298-309	762	18.8
10-12	12.00-12.40	7.5	11	261-00120007-000	250-300	305-315	190	4.8
	12.00-12.40	10	14	261-00120010-000		305-315	254	6.4
	12.00-12.40	12.5	18	261-00120012-000		305-315	317	8.0
	12.00-12.40	15	21	261-00120015-000		305-315	381	9.5
	12.00-12.40	20	28	261-00120020-000		305-315	508	12.7
	12.00-12.40	25	35	261-00120025-000		305-315	635	15.9
	12.00-12.40	30	42	261-00120030-000		305-315	762	19.1
12	12.62-13.02	7.5	11	261-00127507-000	300	321-331	190	5.0
	12.62-13.02	10	15	261-00127510-000		321-331	254	6.7
	12.62-13.02	12.5	18	261-00127512-000		321-331	317	8.3
	12.62-13.02	15	22	261-00127515-000		321-331	381	10.0
	12.62-13.02	20	29	261-00127520-000		321-331	508	13.3
	12.62-13.02	25	37	261-00127525-000		321-331	635	16.6
	12.62-13.02	30	45	261-00127530-000		321-331	762	19.9
12	13.10-13.50	7.5	11	261-00132007-000	300	333-343	190	5.1
	13.10-13.50	10	15	261-00132010-000		333-343	254	6.8
	13.10-13.50	12.5	19	261-00132012-000		333-343	317	8.5
	13.10-13.50	15	22	261-00132015-000		333-343	381	10.2
	13.10-13.50	20	29	261-00132020-000		333-343	508	13.6
	13.10-13.50	25	37	261-00132025-000		333-343	635	17.0
	13.10-13.50	30	45	261-00132030-000		333-343	762	20.3

STANDARD				CATALOG NUMBER	METRIC			
NOM. SIZE INCHES	O.D. RANGE INCHES	WIDTH INCHES	WT. EACH LBS.		NOM. SIZE MM	O.D. RANGE MM	WIDTH MM	WT. EACH KG.
12	13.40-13.80	7.5	11	261-00134007-000	300	340-351	190	5.1
	13.40-13.80	10	15	261-00134010-000		340-351	254	6.9
	13.40-13.80	12.5	18	261-00134012-000		340-351	317	8.5
	13.40-13.80	15	23	261-00134015-000		340-351	381	10.3
	13.40-13.80	20	30	261-00134020-000		340-351	508	13.7
	13.40-13.80	25	38	261-00134025-000		340-351	635	17.1
	13.40-13.80	30	45	261-00134030-000		340-351	762	20.5

## Bolt Numbers

BAND WIDTH INCHES	NUMBER OF STUDS	STUD SIZES
7.5	2	5/8" X 7" or 16mm x 178mm
10	3	
12.5	3	
15	4	
20	5	
25	8	
30	10	