

Silver Series Stainless Steel Braided Flexible Hose

**For Economical
Vibration
Absorption & the
Elimination of
Piping Stress on
Pumps**



- ▶ **Lowest Price**
- ▶ **Medium Duty**
- ▶ **All Standard Installation Length**

MODELS & END FITTINGS	
Model	End Fitting
SKSSPC-MPT	Male Pipe Threads
SKSSPC-FLG	150# Drilling Flanges

KEFLEX™ Silver Series SKSSPC braided flexible pump connectors are constructed of stainless steel annular corrugated metal hose surrounded with a woven braid of high tensile stainless steel. The **KEFLEX™ Silver Series SKSSPC** provides the same **KEFLEX™** standard of quality at an economical price.

Standard end fittings for **KEFLEX™ Silver Series SKSSPC** units are carbon steel male nipples for sizes 1/2" through 2". Sizes 2" and larger have carbon steel plate flanges (5/8" minimum thickness) with ASA 150# bolt hole patterns.

These assemblies are intended for normal to severe pump vibrations. Misalignment should not exceed 1/8" total. Maximum operating temperature is 850° F. For higher pressures or temperatures, consult the factory. For heavy-duty applications requiring significant vibration absorption, noise reduction, pressure differential reduction, and longer life, please select the premiere **KEFLEX™ Gold Series KSSPC**. For greater offset or lateral movements, use **KEFLEX™ KFCS** series flexible connectors.

Silver Series

Stainless Steel Braided Flexible Hose

SKSSPC-MPT

Pipe Size (in.)	OAL (in.)	Part Number	Max Working Pressure @ 70°F*	Approx Weight (lbs.)
1/2	6-1/2	F004SKSSPC	825	.5
3/4	7	F006SKSSPC	600	.8
1	8	F010SKSSPC	580	1
1-1/4	8-1/2	F012SKSSPC	535	1.5
1-1/2	9	F014SKSSPC	510	2.0
2	10-1/2	F020SKSSPCM	442	2.5

*Ratings for constant pressures, use 1/2 of ratings for pulsating pressures and 1/6 of ratings for surge pressures.

SKSSPC-FLG

Pipe Size (in.)	OAL (in.)	Part Number	Max Working Pressure @ 70°F*	Approx Weight (lbs.)
2	9	F020SKSSPCF	442	11
2-1/2	9	F024SKSSPC	390	14
3	9	F030SKSSPC	325	15
4	9	F040SKSSPC	270	20
5	11	F050SKSSPC	185	28
6	11	F060SKSSPC	170	33
8	12	F080SKSSPC	185	52
10	13	F100SKSSPC	180	75
12	14	F120SKSSPC	160	105

*Ratings for constant pressures, use 1/2 of ratings for pulsating pressures and 1/6 of ratings for surge pressures.

Keflex is your single source for braided hose assemblies. Check out our:

- Gold Plus Series flexible hose
- Gold Series flexible hose
- Gold Series Reducing hose
- Ke-Loop L,U,&V expansion loops
- HPH Series Heat Pump/Water hose

