After installing the Magna-Clean Drier run System	After installing the Magna-Clean Drier run System	After installing the Magna-Clean Drier run System
for several hours to circulate the dye throughout	for several hours to circulate the dye throughout	for several hours to circulate the dye throughout
the system.	the system.	the system.
For best viewing results use with SUPCO UVL200	For best viewing results use with SUPCO UVL200	For best viewing results use with SUPCO UVL200
UV Leak Detection Light and Glasses under lower	UV Leak Detection Light and Glasses under lower	UV Leak Detection Light and Glasses under lower
light levels.	light levels.	light levels.
To ease clean up use Highside Dye Wash.	To ease clean up use Highside Dye Wash.	To ease clean up use Highside Dye Wash.
(HS51032) to remove the dye from the leak area.	(HS51032) to remove the dye from the leak area.	(HS51032) to remove the dye from the leak area.
After installing the Magna-Clean Drier run System	After installing the Magna-Clean Drier run System	After installing the Magna-Clean Drier run System
for several hours to circulate the dye throughout	for several hours to circulate the dye throughout	for several hours to circulate the dye throughout
the system.	the system.	the system.
For best viewing results use with SUPCO UVL200	For best viewing results use with SUPCO UVL200	For best viewing results use with SUPCO UVL200
UV Leak Detection Light and Glasses under lower	UV Leak Detection Light and Glasses under lower	UV Leak Detection Light and Glasses under lower
light levels.	light levels.	light levels.
To ease clean up use Highside Dye Wash.	To ease clean up use Highside Dye Wash.	To ease clean up use Highside Dye Wash.
(HS51032) to remove the dye from the leak area.	(HS51032) to remove the dye from the leak area.	(HS51032) to remove the dye from the leak area.
After installing the Magna-Clean Drier run System	After installing the Magna-Clean Drier run System	After installing the Magna-Clean Drier run System
for several hours to circulate the dye throughout	for several hours to circulate the dye throughout	for several hours to circulate the dye throughout
the system.	the system.	the system.
For best viewing results use with SUPCO UVL200	For best viewing results use with SUPCO UVL200	For best viewing results use with SUPCO UVL200
UV Leak Detection Light and Glasses under lower	UV Leak Detection Light and Glasses under lower	UV Leak Detection Light and Glasses under lower
light levels.	light levels.	light levels.
To ease clean up use Highside Dye Wash.	To ease clean up use Highside Dye Wash.	To ease clean up use Highside Dye Wash.
(HS51032) to remove the dye from the leak area.	(HS51032) to remove the dye from the leak area.	(HS51032) to remove the dye from the leak area.