

TA33

Temperature Alarm with Display & Battery Backup

Set your temperature threshold and the TA33 provides reliable protection for your temperature sensitive areas. The battery backup allows continuous monitoring even during power outages. The easy to read display shows current Temperature, Alarm Status, Over/ Under mode indicator and Alarm Set Point and Temperature.

Features/Benefits

- Adjustable range from -40°F to +160°F (-40°C to +71°C)
- Back Lit Display
- 90 db audible alarm
- Adjustable alarm temperature ranges
- Built-in terminals for remote alarm or telephone dialer connection
- Switch for 'No delay' or '1 hour delay'

Applications

- Food Markets, Convenience Stores, Supermarkets
- Restaurants
- Florists, Greenhouses
- Laboratories, Pharmaceutical Storage Facilities
- Refrigerated Transport, Cold Storage Facilities
- Computer Rooms



Specifications

Alarm Adjustment Range	-40°F to 160°F (-40° to 71°C)
Temperature Accuracy	+/- 2°F (+/- 1°C)
Alarm Channels	1
Probe	Precision Thermistor with 6 ft. cable (21301)
Sensor Type	Thermistor
Maximum Probe Extension	200 ft,
Unit Operating Temperature Range	-10°F to +130°F (-23°C to +54°C)
Remote Alarm Connections	Screw type, 120VAC, 10 Amps.
Power	12 V Adapter 120 VAC with 6 ft. cable included (220V available). 24 Hrs 9V Battery backup.
Case	Hi-impact thermoplastic
Mounting	Flat Surface, external holes provided
Dimensions	4.8" x 3.2" x 1.4" (12.2cm x 8.1cm x 3.6cm)
Warranty	1 year

Accessories

21301	Probe
21387	10' Probe Extension
21392	50' Probe Extension
ADTA	Phone Dialer

ADTA

Auto Dialer For Temperature Alarms

- Call up to 4 telephone numbers
- Internal 9V back up battery (not included)
- 16 second message
- LCD display
- Non-Volatile memory for numbers and voice message
- 120V power adapter (included)

