

THE RIGHT CHOICE

SEALED UNIT PARTS CO., INC.

PO Box 21, 2230 Landmark Place Allenwood, NJ 08720 USA 800-333-9125 • www.supco.com

TA44

Single Set Point Temperature Alarm With Digital Display & Remote Wireless Alarm
Provides Reliable Protection For Temperature Sensitive Areas.


Multiple Transmitters & Receivers Can Be Used To Monitor Temperature At Several Locations.

Features / Benefits

- Monitors temperature & alarms in the event of equipment failure
- · Adjustable alarm temperature ranges
- Audible & visual alarms
- 90 db audible alarm
- Over & under temperature modes
- Alarm switch for no delay or 1-hour delay during defrost cycle or when door is left open
- Large LCD digital display
- 6' remote temperature sensor thermistor type used to sense air temperature only. Can be extended up to 200' using 24 AWG stranded wire.
- · Built in terminals for remote alarm or telephone dialer connection
- FCC compliant Class B digital device, pursuent to part 15 of the FCC rules

Applications

- Loss prevention of temperature sensitive products
- · Coolers & Freezers
- Food service
- Horticulture
- Pharmaceutical
- Medical
- Blood banks
- Transportation
- Cold storage
- Computer rooms
- Kennels
- Notification of below freezing temperatures in homes, buildings & remote locations.











R10

TA44 Specifications

Alarm Adjustment Range	-40°F to 160°F (-40°C to 71°C)	
Temperature Accuracy	+/- 2°F (+/- 1°C)	
Operating Temperature Range	-10°F to 130°F (-23°C to 54°C)	
Dimensions	4.9" X 3.1" X 1.5" (12.4cm x 7.9cm x 3.8cm)	
Temperature Units	°F or °C, user selectable	
Power	12V adapter 120 VAC with 6' cable	
Remote Connections	Screw type, 120 VAC, 5 AMPS	
Remote Wireless Alarm	Up to 500' (150m) line of sight remote wireless operation	

Accessories

PART NO	DESCRIPTION
R10	Remote Receiver
20540	Temperature Sensor
SW25	25' Extension Wire
SW50	50' Extension Wire
SW75	75' Extension Wire
SW100	100' Extension Wire
ADTA	Phone Dialer

R10 Specifications

Operating Temperature	-20°F to 160°F (-28°C to 70°C)
Range	
Audible Alarm	110 dB
Dimensions	5" X 2.5" X 1.25"
	(12.7cm x 6.35cm x 3.175cm)
Power	12V adapter 120 VAC
	with 6' cable
Remote Wireless Alarm	Up to 500' (150m) line of
	sight remote wireless operation



R10

ADTA

Auto Dialer For Temperature Alarms

- Call up to 4 telephone numbers
- Internal 9V back up battery (not included)
- 16 second message
- LCD display
- Non-volatile memory for numbers and voice message
- 120V power adapter (included)

