

WHITLAM

FLOW-AIDE™



RECOMMENDED USES:

Evaporators	Boilers
Heat Exchangers	Chillers
Ice Machines	Condensers
Potable Water Lines	Humidifiers
Water Heaters	Tanks

COLOR:

Dark Amber

TEMPERATURE RANGE USE:

Optimal Operating Temperatures between 65°F (18°C) and 95°F (35°C)

CERTIFICATION

NSF/ANSI 60

AVAILABLE SIZES:

Stock #	Size	Items/Case
FLOW32	1 Quart	12
FLOW1	1 Gallon	6

Certified to NSF/ANSI 60 for use as a cleaner in potable water systems. NSF Registered for use in beverage, pharmaceutical, bottling, poultry, and other food processing plants. USFDA has no jurisdiction over the product, since it does not come in contact with food.

J.C. Whitlam Manufacturing Co.

P.O. Box 380
Wadsworth, Ohio 44282

U.S. & Canada

Phone: 800-321-8358

Fax: 800-537-0588

International

Phone: 330-334-2524

Fax: 330-334-3005

BIODEGRADABLE DESCALER

SAFELY REMOVES SCALE, LIME, AND RUST



- Non-Corrosive
- Nontoxic
- Fully Biodegradable*
- Safe to Handle
- Zero V.O.C.



Scale, lime and rust buildup decreases the efficiency of any water based equipment, increases energy usage, and decreases equipment life.

Flow-Aide™ Biodegradable Descaler quickly and safely dissolves water scale, lime, rust, and other water formed deposits, restoring efficiency to most all water based equipment.

Flow-Aide™ Biodegradable Descaler is a non-toxic concentrate which is certified to NSF/ANSI 60 for use as a cleaner in potable water systems.



Safe to Handle

*Flow-Aide™ is biodegradable with a BOD value of 16 mg/l. This normally allows the product to be water flushed down sewers. Check with local ordinances and regulations in your area prior to disposal.

Distributed By:

 **WHITLAM**
PLUMB-PRO
The Industry Standard for Over 100 Years
www.flow-aide.com